

**Application**

Compact semi-recessed luminaire with direct and indirect light distribution. A focusing and dispersing lens collimates the powerful LED light in the center of the reflector for the direct portion of the downlight. At the same time a fraction of the dispersed light is used to illuminate the luminaire glass and generate vertical illuminance. The dual light results in maximum viewing comfort.

**Materials**

Hand-blown crystal glass  
 Marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
 Stainless steel screw clamps  
 Aluminum ceiling mounted driver box

**NRTL** listed to North American Standards, for interior use only

**Weight:** 2.0lbs.

**Electrical**

Operating voltage 120-277VAC  
 Minimum start temperature  $-20^{\circ}\text{C}$   
 LED module wattage 9.6W  
 System wattage 12.0W  
 Controllability 0-10V dimming down to 0.1%  
 Color rendering index  $R_a > 90$   
 Luminaire lumens 1114lm  
 LED service life (L70) 60000hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

Select the desired material finish by using appropriate code number as suffix.

**Available colors**

- White (.1)
- Polished aluminum (.3)
- Stainless steel (.2)



**Semi-recessed downlight · Crystal glass**

	LED	□	A	B	C	D
<b>B12063</b>	9.6W	42°	4 <sup>7</sup> / <sub>8</sub>	3	2	6

Type:  
 BEGA Product:  
 Project:  
 Modified:

