

**Application**

Compact semi-recessed luminaire with direct and indirect light distribution. A focusing and dispersing lens collimates the powerful LED light in the center of the reflector for the direct portion of the downlight. At the same time a fraction of the dispersed light is used to illuminate the luminaire glass and generate vertical illuminance. The dual light results in maximum viewing comfort.

**Materials**

Hand-blown crystal glass  
 Marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
 Stainless steel screw clamps  
 Aluminum ceiling mounted driver box

**NRTL** listed to North American Standards, for interior use only

**Weight:** 2.7 lbs.

**Electrical**

Operating voltage 120-277VAC  
 Minimum start temperature -20° C  
 LED module wattage 17.7 W  
 System wattage 22.0 W  
 Controllability 0-10V dimming down to 0.1%  
 Color rendering index Ra > 90  
 Luminaire lumens 2134 lm  
 LED service life (L70) 60000 hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

Select the desired material finish by using appropriate code number as suffix.

**Available colors**

- White (.1)
- Polished aluminum (.3)
- Stainless steel (.2)



**Semi-recessed downlight · Crystal glass**

	LED	□	A	B	C	D
<b>B12065</b>	17.7 W	49°	7 1/2	3 3/4	2	8 1/2

Type:  
 BEGA Product:  
 Project:  
 Modified:

