#### Application

Luminaires with direct and indirect light, to illuminate both the mounting surface and the desired space. Luminaires in this series are also available with an identical cover made of impact-resistant synthetic material for special applications, add P suffix to luminaire catalog number.

37.8W

43.5W

Ra > 80 3522 lm

60000 hrs

#### Materials

Hand-blown three-ply opal glass Aluminum housing Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, for interior use only

Weight: 13.2 lbs.

# Electrical

LED module wattage System wattage Color rendering index Luminaire lumens LED service life (L70)

### LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

 ${\rm BEGA}$  can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

## Finish

Select the desired material finish by using appropriate code number as suffix.

### Available colors

White (.1)

c •

А

в

Silver (.2)

Type: BEGA Product: Project: Modified:



Ceiling and wall luminaire  $\cdot$  Opal glass  $\cdot$  Direct/Indirect

		LED	A	В	С
B12165	ADA	37.8W	19³/ <sub>4</sub>	33/4	14 <sup>1</sup> / <sub>4</sub>

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com © copyright BEGA 2024 Updated 01/24/24