

Application

Hand-blown three-ply opal glass, in which a wafer thin opalescent layer is molten between two layers of crystal glass, produce a soft distribution of light with high visual comfort. Metal shields with various finishes are gently embedded in the luminaire glass for its support and accentuation. Individually or in groups, these luminaires with their impressive contrasting effect provide atmospheric light for interior applications.

Materials

Hand-blown three-ply opal glass
Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, for interior use only

Weight: 2.4 lbs.

Electrical

Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 7.9W
System wattage 10.5W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 604 lm
LED service life (L70) 60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

- White (.1) Chrome (.3)
- Velvet black (.5)



Wall luminaire · Rounded · Opal glass

		LED	A	B
B12209	ADA	7.9W	7 ⁷ / ₈	2 ¹ / ₄

Type:
BEGA Product:
Project:
Modified:

