

Application

Hand-blown three-ply opal glass, in which a wafer thin opalescent layer is molten between two layers of crystal glass, produce a soft distribution of light with high visual comfort. Metal shields with various finishes are gently embedded in the luminaire glass for its support and accentuation. Individually or in groups, these luminaires with their impressive contrasting effect provide atmospheric light for interior applications.

Materials

Hand-blown three-ply opal glass

NRTL listed to North American Standards, for interior use only

Weight: 2.4 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	16.8 W
System wattage	20.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	1283 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

- White (.1)
- Velvet black (.5)
- Chrome (.3)



Wall luminaire · Rounded · Opal glass

		LED	A	B
B12210	ADA	16.8 W	12 ⁵ / ₈	2 ¹ / ₂

Type:
 BEGA Product:
 Project:
 Modified:

