

Application

Recessed ceiling luminaire with asymmetric narrow beam light distribution. The patented (US 2016/0327243) BEGA Vortex Optics® rotates a parabolic reflector around the vertical axis to form a complex vortex shape. The vortex balances maximum efficiency with optimal glare control while eliminating shadows and artifacts in a uniquely square distribution.

Materials

- Clear safety glass
- Die-cast aluminum
- Stainless steel screw clamps
- BEGA Vortex Optics®
- Pure anodized aluminum reflector surface

NRTL listed to North American Standards, for interior use only

Weight: 4.4 lbs.

Electrical

LED module wattage	23.2 W
System wattage	28.0 W
Color rendering index	Ra > 80
Luminaire lumens	1931 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired trim ring material finish by using appropriate code number as suffix.

Available colors

- White (.1)
- Polished aluminum (.3)
- Stainless steel (.2)

Type:

BEGA Product:

Project:


Modified:

Available options

- DALI Digital addressable lighting interface
- FSC Fusing

Included (available for pre-shipment)

- CP12199 Ceiling pan (120V or 277V, specify voltage)



Downlight · Asymmetric				
	LED	□	A	B
B12235	23.2 W	31°x30°	7	5 1/2

