Application

Cost-effective LED wall luminaires that distribute their light upwards and downwards on the wall. Two crystal glass elements enhance the high-precision housings made of cast aluminum and lend them their distinctive character.

Materials

Pressed crystal glass with white ceramic coating on one side Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy Silicone applied robotically to casting, plasma treated for increased adhesion

NRTL listed to North American Standards, for interior use only

Weight: 3.7 lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 8.4 W
System wattage 15.7 W

Controllability 0-10V, TRIAC, and ELV dimmable

Color rendering index Ra > 90 Luminaire lumens 649 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

White (.1) Palladium (.4)

Type:

BEGA Product:

Project:

Modified:

Included (available for pre-shipment)

B19545 Narrow opening wiring box





Wall luminaire · Light emission on two sides

LED A B C **B12277** 8.4W 7⁷/₈ 2¹/₂ 4³/₈