

Application

Designed for low mounting heights for interior and exterior locations, the unshielded luminaire has a directing and guiding lighting effect. The illuminance level on the lit surface is lower, but the ambient brightness is greater with increased vertical illuminance.

Materials

Clear safety glass with white ceramic coating
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 Corrosion-resistant 304 grade stainless steel
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 64

Weight: 5.5 lbs.

Electrical

LED module wattage	10.1 W
System wattage	11.5 W
Color rendering index	Ra > 80
Luminaire lumens	91 lm
LED service life (L70)	60000 hrs


LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3)
 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.



Recessed wall luminaire · Unshielded

		LED	A	B	C
B22132	ADA	10.1 W	12 ³ / ₄	3 ¹ / ₈	4

Type:

BEGA Product:

Project:

Modified:

Available accessories

B19601 Concrete protection cover

See individual accessory spec sheet for details.

Included (available for pre-shipment)

BB2035LED Installation housing

