

**Application**

Designed for low mounting heights for interior and exterior locations, the shielded light distribution is ideal for the glare-free illumination of ground surfaces, building entrances, stairs, and footpaths.

**Materials**

Clear safety glass with optical texture  
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 Corrosion-resistant 304 grade stainless steel  
 High temperature silicone gasket  
 Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 64

**Weight:** 4.5 lbs.

**Electrical**

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	3.4 W
System wattage	4.9 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	9 lm
LED service life (L70)	60000 hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

#4 brushed stainless steel. Custom colors are not available.



**Recessed wall luminaire · Shielded**

		LED	A	B	C
<b>B22135</b>	<b>ADA</b>	3.4 W	7 1/2	3 1/8	4

Type:

BEGA Product:

Project:

Modified:

**Available options**

- AMB Amber LED
- FSC Fusing

**Available accessories**

- B19535 Concrete protection cover

See individual accessory spec sheet for details.

**Included (available for pre-shipment)**

- BB2033LED Installation housing

