Application

This wall mounted luminaire has a directed light distribution and is designed for general illumination of pathways, walkways, and plazas.

Materials

Clear safety glass with white ceramic coating

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy

High temperature silicone gasket

Mechanically captive stainless steel fasteners

Galvanized zinc-plated mounting bracket

Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 1.4 lbs.

Electrical

Operating voltage 24VDC (remote power supply req.)

Minimum start temperature -40° C
LED module wattage 3.0 W
System wattage 4.0 W
Controllability Non-Dimming

Color rendering index Ra > 80 Luminaire lumens 92 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:

Type:

BEGA Product:

Project: Modified:

Available options


CUS Custom finish

MGU Marine grade undercoat

RAL RAL finish

Available accessories

B19580 Remote driver box · Static white B19591 Remote driver box · Static white See individual accessory spec sheet for details.





Wall luminaire · Directed light • 24V DC