

**Application**

This luminaire can be utilized at low or high mounting heights to illuminate pathways and corridors for safety and egress purposes.

**Materials**

Clear safety glass with matte finish  
 Marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
 High temperature silicone gasket  
 Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 3.5 lbs.

**Electrical**

Operating voltage 120-277V AC  
 Minimum start temperature  $-30^{\circ}\text{C}$   
 LED module wattage 12.3W  
 System wattage 16.0W  
 Controllability 0-10V dimmable  
 Color rendering index  $R_a > 80$   
 Luminaire lumens 939lm  
 LED service life (L70) 60000hrs

**LED color temperature**

4000K (K4)  
 3500K (K35)  
 3000K (K3)  
 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**


All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

**Available options**

CUS	Custom finish
MGU	Marine grade undercoat
RAL	RAL finish



**Wall luminaire · Directed light**

		LED	A	B	C
<b>B22385</b>	<b>ADA</b>	12.3W	11 <sup>3</sup> / <sub>4</sub>	4 <sup>3</sup> / <sub>4</sub>	3

