

Application

Designed for indirect or direct lighting effects for interior and exterior locations. This wall luminaire is for illuminating surfaces adjacent to the installation surface, such as ceilings, arches, and canopies. DarkSky Approved when installed facing down (2700K and 3000K only)

Materials

Clear safety glass with white ceramic coating
 Marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners
 Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 11.5lbs.

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -30°C
 LED module wattage 50.6W
 System wattage 54.0W
 Controllability 0-10V dimmable
 Color rendering index $Ra > 80$
 Luminaire lumens 2982lm
 LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3) (DarkSky Approved)
 2700K (K27) (DarkSky Approved)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
 Silver (SLV) White (WHT)
 RAL: CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

CUS Custom finish
 FSC Fusing
 MGU Marine grade undercoat
 RAL RAL finish



Wall washer · Asymmetric				
	LED	A	B	C
B22434	50.6W	10 ¹ / ₄	8 ¹ / ₂	9 ⁵ / ₈

