Application

Designed for indirect or direct lighting effects for interior and exterior locations. This wall luminaire is for illuminating wall surfaces, with the mounting surface also acting as the reflection surface. DarkSky Approved when installed facing down (2700K and 3000K only)

Materials

Clear safety glass with white ceramic coating Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy High temperature silicone gasket Mechanically captive stainless steel fasteners Galvanized zinc-plated mounting bracket Pure anodized aluminum reflector

 $\ensuremath{\mathsf{NRTL}}$ listed to North American Standards, suitable for wet locations Protection class IP 65

Weight: 4.9 lbs.

Electrical

Operating voltage Minimum start temperature LED module wattage System wattage Controllability Color rendering index Luminaire lumens LED service life (L70) 120, 220-240 OR 277 VAC -30° C 17.9 W 21.0 W 0-10V dimmable Ra > 90 2030 Im 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) (DarkSky Approved) 2700K (K27) (DarkSky Approved)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Silver (SLV) RAL: Bronze (BRZ) White (WHT) CUS: Type: BEGA Product: Project: Modified:


Available options

CUS	Custom finish
MGU	Marine grade undercoat
RAL	RAL finish

Included (available for pre-shipment)

B19538 Small opening wiring box





Wall washer · Symmetric						
	LED	A	В	С		
B22449	17.9W	6 ¹ / ₂	6 ⁵ / ₈	71/8		

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com © copyright BEGA 2024 Updated 01/29/24