

**Application**

Impact-resistant ceiling and wall luminaire with unshielded light distribution and safety guard. Arranged individually or in groups, they are great design elements for a host of lighting applications.

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65

**Weight:** 2.4 lbs.

**Electrical**

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	2.9W
System wattage	4.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	184 lm
LED service life (L70)	60000hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:


BEGA Product:

Project:

Modified:

**Available options**

CUS	Custom finish
MGU	Marine grade undercoat
RAL	RAL finish



**Impact-resistant ceiling and wall luminaire · Glass**

		LED	A	B	C
<b>B22686</b>	ADA	2.9W	8 <sup>3</sup> / <sub>4</sub>	5 <sup>1</sup> / <sub>8</sub>	4

