

Application

The material thickness and strong crystal glass makes this impact-resistant luminaire extremely robust. Arranged individually or in groups, they are great design elements for a host of lighting applications.

Materials

Pressed crystal glass with white ceramic coating on one side
 Die-cast aluminum
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 6.2 lbs.

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -30° C
 LED module wattage 8.4 W
 System wattage 11.0 W
 Controllability 0-10V, TRIAC, and ELV dimmable
 Color rendering index Ra > 80
 Luminaire lumens 405 lm
 LED service life (L70) 60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

- CUS Custom finish
- FSC Fusing
- MGU Marine grade undercoat
- RAL RAL finish



| Impact-resistant ceiling and wall luminaire · Unshielded | | | | |
|--|-------|-------------------------------|--------------------------------|-------------------------------|
| | LED | A | B | C |
| B22751 | 8.4 W | 6 ³ / ₈ | 11 ³ / ₈ | 4 ¹ / ₂ |

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com