Application

Wall luminaires for a host of applications - arranged individually or in groups. The luminaires can be installed in a horizontal or vertical position.

Materials

Hand-blown three-ply opal glass Aluminum housing

NRTL listed to North American Standards, for interior use only

Weight: 4.4 lbs.

Electrical

Operating voltage Minimum start temperature LED module wattage System wattage Controllability Color rendering index Luminaire lumens LED service life (L70)

120-277VAC -20° C 7.8W 12.7 W 0-10V dimmable Ra > 80 723 lm 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

White (.1) Chrome (.3) Stainless steel (.2)

Type: **BEGA Product:** Project: Modified:

Included (available for pre-shipment) B19537

Narrow opening wiring box



	B	$\Box\bigcirc$
А		• с •

Linear wall luminaire · Opal glass							
	LED	А	В	С			
B23250	7.8W	19 ³ / ₄	23/4	4 ¹ / ₈			

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us, com © copyright BEGA 2024 Updated 01/24/24