Application

Ceiling and wall luminaires designed for the illumination of rooms, bathrooms, stairways, and other interior spaces characterized by their shallow projection featuring hand-blown, three-ply opal glass with satin matte finish.

Materials

Hand-blown opal glass Aluminum housing Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, for interior use only

Weight: 11.5 lbs.

Electrical

Operating voltage Minimum start temperature LED module wattage System wattage Controllability Color rendering index Luminaire lumens LED service life (L70) 120-277V AC -30° C 37.8 W 43.5 W 0-10V dimmable Ra > 90 3637 Im 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

с ·

White finish. Custom colors not available.

Type: BEGA Product: Project: Modified:



Ceiling and wall luminaire · Opal glass								
		٨	_					

		LED	A	В	С
B23297	ADA	37.8W	18 ¹ / ₂	33/4	14 ¹ / ₄

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com © copyright BEGA 2024 Updated 01/17/24