

**Application**

Ceiling luminaire with direct/indirect light distributions. A focusing/dispersing lens collimates the powerful LED light in the center of the reflector for the direct portion of the downlight. At the same time, a fraction of the dispersed light is used to illuminate the luminaire glass and generate vertical illuminance. The dual light distribution results in maximum viewing comfort.

**Materials**

Hand-blown crystal glass  
 Aluminum housing  
 Pure anodized aluminum reflector

**NRTL listed** to North American Standards, for interior use only

**Weight:** 3.8lbs.

**Electrical**

Operating voltage 120-277VAC  
 Minimum start temperature -30° C  
 LED module wattage 19.0W  
 System wattage 23.5W  
 Controllability 0-10V dimmable  
 Color rendering index Ra > 90  
 Luminaire lumens 1749lm  
 LED service life (L70) 60000hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

Select the desired material finish by using appropriate code number as suffix.

**Available colors**

- White (.1)
- Polished aluminum (.3)
- Stainless steel (.2)



**Ceiling luminaire · Crystal glass · Direct/Indirect**

|               | LED   | A     | B     |
|---------------|-------|-------|-------|
| <b>B23576</b> | 19.0W | 7 1/2 | 6 1/4 |

Type:  
 BEGA Product:  
 Project:  
 Modified:

