

**Application**

Ceiling luminaires with direct/indirect light distributions. A focusing/dispersing lens collimates the powerful LED light in the center of the reflector for the direct portion of the downlight. At the same time, a fraction of the dispersed light is used to illuminate the luminaire glass and generate vertical illuminance. The dual light distribution results in maximum viewing comfort.

**Materials**

Hand-blown three-ply opal glass  
 Aluminum housing  
 Pure anodized aluminum reflector

**NRTL** listed to North American Standards, for interior use only

**Weight:** 1.1 lbs.

**Electrical**

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	3.0W
System wattage	5.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	265lm
LED service life (L70)	60000 hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

Select the desired material finish by using appropriate code number as suffix.

**Available colors**

- White (.1)    Stainless steel (.2)
- Polished aluminum (.3)

Type:

BEGA Product:

Project:

Modified:



**Ceiling luminaire · Opal glass · Direct/Indirect**

	LED	A	B
<b>B23619</b>	3.0W	4	4 1/4

**Included (available for pre-shipment)**  
 B19538      Small opening wiring box

