# Application

Wall luminaires with directed narrow beam light distribution on one side that can be oriented upward or downward. Arranged individually or in groups, they are great design elements for a host of lighting applications.

## Materials

Clear safety glass

Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy Mechanically captive stainless steel fasteners

High temperature silicone gasket Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 6.6 lbs.

Electrical
Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 18.1 W
System wattage 21.0 W

Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 1738 lm
LED service life (L70) 60000 hrs

### LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

#### Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

# Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:

Type:

**BEGA Product:** 

Project: Modified:

### Available options

CUS Custom finish FSC Fusing

MGU Marine grade undercoat

RAL RAL finish

# Available accessories

B79547 Surface mounted wiring box See individual accessory spec sheet for details.

## Included (available for pre-shipment)

B19537 Narrow opening wiring box





Wall luminaire · Narrow beam upward or downward