


BEGA

File: 24052K4_BEGA_IES.ies

TEST: 24052K4
TEST LAB: BEGA
DATE: 06/17/2025
LUMINAIRE: 24052K4
LAMP: 5.6W LED




Characteristics

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	164
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	23
Total Luminaire Watts	10
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	0.14
Spacing Criterion (90-270)	1.18
Spacing Criterion (Diagonal)	0.66
Basic Luminous Shape	Sphere
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	0.48 ft (Diameter)
Luminous Height	0.21 ft (Diameter)

Lum. Classification System (LCS)


LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	18.8	N.A.	11.4
FM (30-60)	8.2	N.A.	5.0
FH (60-80)	0.1	N.A.	0.1
FVH(80-90)	< 0.05	N.A.	0.0
BL (0-30)	82.3	N.A.	50.2
BM (30-60)	54.5	N.A.	33.2
BH (60-80)	0.3	N.A.	0.2
BVH(80-90)	< 0.05	N.A.	0.0
UL (90-100)	0.0	N.A.	0.0
UH (100-180)	0.0	N.A.	0.0
Total	164.2	N.A.	100.0

BUG Rating B0-U0-G0



Grid Spacing: 3 ft.

Isofootcandle grid on wall



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.


BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2025

06/17/2025

BEGA

File: 24052K35_BEGA_IES.ies

TEST: 24052K4
TEST LAB: BEGA
DATE: 06/17/2025
LUMINAIRE: 24052K35
LAMP: 5.6W LED




Characteristics

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	157
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	22
Total Luminaire Watts	10
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	0.14
Spacing Criterion (90-270)	1.18
Spacing Criterion (Diagonal)	0.66
Basic Luminous Shape	Sphere
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	0.48 ft (Diameter)
Luminous Height	0.21 ft (Diameter)

Lum. Classification System (LCS)


LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	18.8	N.A.	11.4
FM (30-60)	8.2	N.A.	5.0
FH (60-80)	0.1	N.A.	0.1
FVH(80-90)	< 0.05	N.A.	0.0
BL (0-30)	82.3	N.A.	50.2
BM (30-60)	54.5	N.A.	33.2
BH (60-80)	0.3	N.A.	0.2
BVH(80-90)	< 0.05	N.A.	0.0
UL (90-100)	0.0	N.A.	0.0
UH (100-180)	0.0	N.A.	0.0
Total	164.2	N.A.	100.0

BUG Rating B0-U0-G0



Grid Spacing: 3 ft.

Isofootcandle grid on wall



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.


BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2025

06/17/2025

BEGA

File: 24052K3_BEGA_IES.ies

TEST: 24052K4
TEST LAB: BEGA
DATE: 06/17/2025
LUMINAIRE: 24052K3
LAMP: 5.6W LED




Characteristics

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	150
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	21
Total Luminaire Watts	10
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	0.14
Spacing Criterion (90-270)	1.18
Spacing Criterion (Diagonal)	0.66
Basic Luminous Shape	Sphere
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	0.48 ft (Diameter)
Luminous Height	0.21 ft (Diameter)

Lum. Classification System (LCS)


LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	17.1	N.A.	11.4
FM (30-60)	7.5	N.A.	5.0
FH (60-80)	0.1	N.A.	0.1
FVH(80-90)	< 0.05	N.A.	0.0
BL (0-30)	75.2	N.A.	50.2
BM (30-60)	49.7	N.A.	33.2
BH (60-80)	0.2	N.A.	0.2
BVH(80-90)	< 0.05	N.A.	0.0
UL (90-100)	0.0	N.A.	0.0
UH (100-180)	0.0	N.A.	0.0
Total	149.8	N.A.	100.0

BUG Rating B0-U0-G0



Grid Spacing: 3 ft.

Isofootcandle grid on wall



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.


BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2025

06/17/2025

BEGA

File: 24052K4_BEGA_IES.ies

TEST: 24052K4
TEST LAB: BEGA
DATE: 06/17/2025
LUMINAIRE: 24052K27
LAMP: 5.6W LED




Characteristics

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	138
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	20
Total Luminaire Watts	10
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	0.14
Spacing Criterion (90-270)	1.18
Spacing Criterion (Diagonal)	0.66
Basic Luminous Shape	Sphere
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	0.48 ft (Diameter)
Luminous Height	0.21 ft (Diameter)

Lum. Classification System (LCS)


LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	15.8	N.A.	11.4
FM (30-60)	6.9	N.A.	5.0
FH (60-80)	0.1	N.A.	0.1
FVH(80-90)	< 0.05	N.A.	0.0
BL (0-30)	69.2	N.A.	50.2
BM (30-60)	45.8	N.A.	33.2
BH (60-80)	0.2	N.A.	0.2
BVH(80-90)	< 0.05	N.A.	0.0
UL (90-100)	0.0	N.A.	0.0
UH (100-180)	0.0	N.A.	0.0
Total	138.0	N.A.	100.0

BUG Rating B0-U0-G0



Grid Spacing: 3 ft.

Isofootcandle grid on wall



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2025

06/17/2025