

Application

Recessed wall luminaire with asymmetric forward throw distribution for superior illumination of ground surfaces from an extremely low mounting height. The optimal mounting height between 1' and 1.5' above finished grade. Separate installation housing allows for seamless coordination into construction and easy maintenance.

Materials

Clear safety glass with printed optical texture
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
 Stainless steel screw clamps
 Mechanically captive stainless steel fasteners
 Composite installation housing
 Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 1.7 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	7.2W
System wattage	8.8W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	489lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

- | | |
|--------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| RAL: | CUS: |

Type:

BEGA Product:

Project:

Modified:

Available options

- | | |
|-----|------------------------|
| CUS | Custom finish |
| FSC | Fusing |
| MGU | Marine grade undercoat |
| RAL | RAL finish |

Included (available for pre-shipment)

- | | |
|---------|----------------------|
| BB24064 | Installation housing |
|---------|----------------------|



Recessed wall luminaire · Extended throw

	LED	A	B	C
B24064	7.2W	10 ¹ / ₈	2 ³ / ₄	5

