

**Application**

Recessed wall luminaire with shielded light for glare-free illumination of ground surfaces and way finding.

**Materials**

BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection

**NRTL** listed to North American Standards, suitable for wet locations

Protection class IP 65

**Weight:** 3.3 lbs.

**Electrical**

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	3.7 W
System wattage	6.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	42 lm
LED service life (L70)	60000 hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:

BEGA Product:

Project:


Modified:

**Available options**

CUS	Custom finish
MGU	Marine grade undercoat
RAL	RAL finish

**Included (available for pre-shipment)**

BB24012 Installation housing



**Recessed wall luminaire · Shielded**

	LED	A	B
<b>B24102</b>	ADA 3.7 W	7 <sup>3</sup> / <sub>8</sub>	5 <sup>1</sup> / <sub>2</sub>

