

**Application**

Designed for accent lighting of walls and facades. Two narrow beams of light produce a striking pattern on the installation surface in any orientation.

**Materials**

Clear safety glass with optical texture  
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 Silicone applied robotically to casting, plasma treated for increased adhesion  
 Mechanically captive stainless steel fasteners  
 High temperature silicone gasket  
 Galvanized zinc-plated mounting bracket  
 Silicone optic with excellent high temperature and UV stability

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 3.5 lbs.

**Electrical**

Operating voltage 120-277V AC  
 Minimum start temperature -30° C  
 LED module wattage 4.0W  
 System wattage 8.0W  
 Controllability 0-10V dimmable  
 Color rendering index Ra > 80  
 Luminaire lumens 182lm  
 LED service life (L70) 60000 hrs

**LED color temperature**

4000K (K4)  
 3500K (K35)  
 3000K (K3)  
 2700K (K27)


**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

Black (BLK) Bronze (BRZ)  
 Silver (SLV) White (WHT)  
 RAL: CUS:



**Wall luminaire · Two 15° ports**

	LED	A	B
<b>B24177</b>	4.0W	7 1/8	2 7/8

Type:  
 BEGA Product:  
 Project:  
 Modified:

