

Application

Recessed wall luminaire with shielded light distribution for glare-free illumination of ground surfaces, building entrances, stairs and pathways.

Materials

Clear safety glass with optical texture
 BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
 Mechanically captive stainless steel fasteners
 Stainless steel screw clamps
 Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 2.2 lbs.

Electrical

Operating voltage 120-277V AC
 Minimum start temperature -40° C
 LED module wattage 2.9W
 System wattage 5.0W
 Controllability 0-10V dimmable
 Color rendering index Ra > 80
 Luminaire lumens 274 lm
 LED service life (L70) 60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:



Recessed wall luminaire · Shielded

	LED	A	B	C
B24202	2.9W	5 ⁷ / ₈	5 ⁷ / ₈	5 ¹ / ₄

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com © copyright BEGA 2024 Updated 03/04/24

Type:

BEGA Product:

Project:

Modified:

Available options

- CUS Custom finish
- MGU Marine grade undercoat
- RAL RAL finish

Included (available for pre-shipment)

- BB24215 Installation housing

