# Ceiling and wall luminaire · Unshielded with safety guard · crystal glass

# Application

A robust and timeless ceiling and wall luminaire for a host of lighting applications. Fasteners are not visible on the front of the housing adding to the elegance of this design.

### Materials

Pressed crystal glass

Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy High temperature silicone gasket

Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 5.2 lbs. Electrical

Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 11.9 W
System wattage 14.0 W

Controllability 0-10V, TRIAC, and ELV dimmable

Color rendering index Ra > 80 Luminaire lumens 1210 lm LED service life (L70) 60000 hrs

## LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

### Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint

## Available colors

 Black (BLK)
 Bronze (BRZ)

 Silver (SLV)
 White (WHT)

 RAL:
 CUS:

Type:

**BEGA Product:** 

Project: Modified:

# Available options


CUS Custom finish

FSC Fusing

MGU Marine grade undercoat

RAL RAL finish





Ceiling and wall luminaire  $\cdot$  Unshielded with safety guard  $\cdot$  crystal glass

	LED	Α	В	С
B24354	11.9W	11 <sup>3</sup> / <sub>4</sub>	71/8	41/4