BEGA

Application

Designed to provide general illumination and visual interest for interior and exterior locations. A narrow beam light distribution downward is ideal for general illumination of pathways and corridors, while a very narrow distribution upward is ideal for highlighting various architectural features and creating patterns of light.

Materials

Clear safety glass

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy High temperature silicone gasket

Mechanically captive stainless steel fasteners

Silicone applied robotically to casting, plasma treated for increased adhesion

Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 64

Weight: 1.7 lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 3.8 W
System wattage 5.5 W

Controllability 0-10V dimmable

Color rendering index Ra > 80 Luminaire lumens 276 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:

В .

Ċ.

Wall luminaire · Very narrow beam upward · Narrow downward

		LED		Α	В	С
B24594	ADA	3.8 W	13°/20°	3	5 ¹ / ₈	33/4

Type:

BEGA Product:

Project: Modified:

Available options

CUS Custom finish

FSC Fusing

MGU Marine grade undercoat

RAL RAL finish

