

Application

Recessed ceiling luminaire with very wide beam light distribution designed for downlighting atriums, canopies, passages and other interior and exterior locations.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Stainless steel screw clamps
- High temperature silicone gasket
- Silicone optic with excellent high temperature and UV stability
- Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 2.2 lbs.

Electrical

LED module wattage	8.3 W
System wattage	9.7 W
Color rendering index	Ra > 80
Luminaire lumens	1155 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:

BEGA Product:

Project:


Modified:

Available options

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL finish

Included (available for pre-shipment)

CP24817



Downlight · Very wide beam

	LED	□	A	B	C
B24829	8.3 W	59°	5 ^{5/8}	5	18