

**Application**

Wall luminaires with shielded light distribution. The shape of the lantern is unmatched in its diversity. These luminaires are particularly suitable for illuminating areas in front of the mounting surface such as courtyards or alongside and above doors.

**Materials**

Hand-blown three-ply opal glass  
Aluminum housing

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 44

**Weight:** 2.2 lbs.

**Electrical**

Operating voltage 120-277V AC  
Minimum start temperature -30° C  
LED module wattage 3.0W  
System wattage 5.0W  
Controllability 0-10V dimmable  
Color rendering index Ra > 80  
Luminaire lumens 375lm  
LED service life (L70) 60000hrs

**LED color temperature**

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

BEGA Black polyester powder coat finish. Custom colors not available.

**Available colors**


Black (BLK)

Type:

BEGA Product:

Project:

Modified:



**Wall luminaire · Shielded**

	LED	A	B	C	D
<b>B31014</b>	3.0W	7	8 1/2	10 1/4	3 1/8

**Available options**

CUS Custom finish  
MGU Marine grade undercoat  
RAL RAL finish

