

Application

A ceiling and wall luminaire with copper and opal glass. Backlight onto the wall or ceiling surface creates a contrast between the opal glass, the shield, and the mounting surface when illuminated.

Materials

Three-ply opal glass with satin matte finish
 A380 aluminum alloy
 99.9% pure copper
 High temperature silicone gasket
 Stainless steel mounting plate

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 6.8 lbs.

Electrical

Operating voltage 120-277V AC
 Minimum start temperature -30° C
 Maximum ambient temperature 50° C
 LED module wattage 14.2 W
 System wattage 18.0 W
 Controllability 0-10V dimmable
 Color rendering index Ra > 80
 Luminaire lumens 1489 lm
 LED service life (L70) 60000 hrs


LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3)
 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Natural copper finish. Time and weather factors will create the natural patina of copper.



Ceiling and wall luminaire · Opal glass

		LED	A	B	C
B31042	ADA	14.2 W	12 ⁷ / ₈	3 ⁵ / ₈	9 ⁷ / ₈

Type:

BEGA Product:

Project:

Modified:

Available options

DALI Digital addressable lighting interface
 ELV/TRIAC Electronic low voltage/TRIAC
 FSC Fusing

