

Application

Wall luminaires with unshielded light distribution. These luminaires are ideally suited for illuminating entrances, arcades and walkways.

Materials

Hand-blown three-ply opal glass  
Aluminum housing  
Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 44

Weight: 7.7 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	22.0W
System wattage	25.5W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	1585lm
LED service life (L70)	60000hrs

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK)

Type:  
BEGA Product:  
Project:  
Modified:



Wall luminaire · Unshielded					
	LED	A	B	C	D
B31075	22.0W	4 1/4	25 3/8	6 1/2	4 3/8

