

Application

Wall luminaires with unshielded light distribution. A combination of materials in perfect harmony with this classic luminaire shape. Whether as single luminaires or arranged in groups, these luminaires are perfect architectural elements.

Materials

Hand-blown three-ply opal glass
 99.9% pure copper
 High-strength, C90700 bronze

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 44

Weight: 13.4 lbs.

Electrical

Operating voltage 120-277V AC
 Minimum start temperature -30° C
 LED module wattage 3.9W
 System wattage 11.0W
 Controllability 0-10V dimmable
 Color rendering index Ra > 80
 Luminaire lumens 537 lm
 LED service life (L70) 60000 hrs


LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3)
 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Natural cast bronze and copper. Time and weather factors will create the natural patina of bronze and copper.



Cast bronze and copper wall luminaire · Unshielded

	LED	A	B	C	D
B31218	3.9W	9 ⁷ / ₈	21	12 ¹ / ₈	5 ¹ / ₈

Type:
 BEGA Product:
 Project:
 Modified:

