

**Application**

Ceiling and wall luminaires with unshielded light distribution. Whether as single luminaires or arranged in groups, these luminaires are robust and perfect architectural elements.

**Materials**

Pressed crystal glass with white ceramic coating on one side  
 99.9% pure copper  
 High-strength, free machining C38500 brass

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 64

**Weight:** 3.5 lbs.

**Electrical**

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	6.3 W
System wattage	8.3 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	399 lm
LED service life (L70)	60000 hrs

**LED color temperature**


4000K (K4)  
 3500K (K35)  
 3000K (K3)  
 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

Natural copper with cast bronze and brass. Time and weather factors will create the natural patina of copper and bronze.

Type:  
 BEGA Product:  
 Project:  
 Modified:



**Ceiling and wall luminaire · Unshielded**

	LED	A	B
<b>B31333</b>	6.3 W	8 <sup>5</sup> / <sub>8</sub>	4 <sup>3</sup> / <sub>4</sub>

