

**Application**

LED recessed wall luminaire with unshielded light and louvers for use as location luminaires for means of way finding.

**Materials**

Luminaire housing constructed of die-cast aluminum marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
 White safety glass  
 Silicone applied robotically to plasma treated casting for increased adhesion  
 High temperature silicone gasket  
 Mechanically captive stainless steel fasteners  
 Stainless steel screw clamps  
 Composite installation housing

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP65  
 Weight: 6.0 lbs

**Electrical**

Operating voltage 120-277VAC  
 Minimum start temperature  $-30^{\circ}\text{C}$   
 LED module wattage 9.8W  
 System wattage 13.0W  
 Controllability 0-10V dimmable  
 Color rendering index  $Ra > 80$   
 Luminaire lumens 113 lumens (3000K)  
 Lifetime at  $Ta=15^{\circ}\text{C}$   $> 500,000$  h (L70)  
 Lifetime at  $Ta=40^{\circ}\text{C}$  285,000 h (L70)

**LED color temperature**


- 2700K - Product number + **K27**
- 3000K - Product number + **K3**
- 3500K - Product number + **K35**
- 4000K - Product number + **K4**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.


Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



**LED recessed wall luminaires · unshielded location luminaires**

	LED	A	B	C
<b>33052</b>	9.8W	20½	5	5½

Type:  
 BEGA Product:  
 Project:  
 Modified:



Fully enclosed luminaire with installation housing ensures seamless integration and weathertight operation.

