Application

Recessed wall luminaire with asymmetric light distribution that is ideal for the illumination of ground surfaces, building entrances, stairs and footpaths. Separate installation housing allows for seamless coordination into construction and easy maintenance.

Materials

BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection

Composite installation housing Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations

120-277VAC

Protection class IP 65

Weight: 1.5 lbs. Electrical

Operating voltage Minimum start temperature

-40° C LED module wattage 4.1 W System wattage 6.0W Controllability 0-10V dimmable

Color rendering index Ra > 80Luminaire lumens 231 lm 60000 hrs LED service life (L70)

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ) Silver (SLV) White (WHT) RAL: CUS:

Type:

BEGA Product:

Project: Modified:

Available options

AMB Amber LED CUS Custom finish


FSC Fusing

MGU Marine grade undercoat

RAL RAL finish

Included (available for pre-shipment)

BB24063 Installation housing





Recessed wall luminaire · Directed light					
	LED	Α	В	С	
B33053	4.1 W	6 ⁵ / ₈	23/4	5	