

Application

Recessed wall luminaire with unshielded light distribution for the illumination of ground surfaces, building entrances, stairs and footpaths. Separate installation housing allows for seamless coordination into construction and easy maintenance.

Materials

BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 1.2 lbs.

Electrical

Operating voltage 120-277VAC
Minimum start temperature -40° C
LED module wattage 4.0W
System wattage 6.0W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 331 lm
LED service life (L70) 60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

- CUS Custom finish
- FSC Fusing
- MGU Marine grade undercoat
- RAL RAL finish

Included (available for pre-shipment)

- BB24063 Installation housing



Recessed wall luminaire · Unshielded

	LED	A	B	C
B33109	4.0W	6 ⁵ / ₈	2 ³ / ₄	5

