Application

Recessed wall luminaire with unshielded light to be used as location luminaires for means of way finding. Separate installation housing allows for seamless coordination into construction and easy maintenance.

Materials

Clear safety glass with white ceramic coating

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection

Mechanically captive stainless steel fasteners

Stainless steel screw clamps

Composite installation housing

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 2.1 lbs. Electrical

Operating voltage 120-277V AC
Minimum start temperature -40° C
LED module wattage 3.8 W
System wattage 6.0 W

Controllability 0-10V dimmable

Color rendering index Ra > 80 Luminaire lumens 329 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:

Type:

BEGA Product:

Project: Modified:

Available options

AMB Amber LED Custom finish


FSC Fusing

MGU Marine grade undercoat

RAL RAL finish

Included (available for pre-shipment)

BB24065 Installation housing





Recessed wall luminaire · Location luminaire

	LED	А	В	С	
B33166	3.8W	121/2	23/4	5	