

Application

This luminaire features flush mounted glass which distributes the light onto the installation surface uniformly with a wide-spread light distribution. Luminaire can be mounted with the light output upwards or downwards.

Materials

Clear safety glass with optical texture
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 1.8 lbs.

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -30° C
 LED module wattage 3.0W
 System wattage 5.8W
 Controllability 0-10V dimmable
 Color rendering index Ra > 80
 Luminaire lumens 348 lm
 LED service life (L70) 60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:

Type:

BEGA Product:

Project:


Modified:

Available options

- CUS Custom finish
- MGU Marine grade undercoat
- RAL RAL finish

Included (available for pre-shipment)

- B19542 Narrow opening wiring box



Wall luminaire · Directed light

	LED	A	B	C
B33223	3.0W	4	2 ³ / ₈	5 ¹ / ₈

