Application

This wall luminaire with a symmetric light distribution can be used to illuminate façade and wall surfaces, with the installation surface also acting as a reflection surface. Able to be installed in either direction for uplight or downlight applications.

Materials

Clear safety glass

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy High temperature silicone gasket

Mechanically captive stainless steel fasteners

Silicone applied robotically to casting, plasma treated for increased adhesion

Galvanized zinc-plated mounting bracket

Pure anodized aluminum reflector

 $\ensuremath{\mathsf{NRTL}}$ listed to North American Standards, suitable for wet locations Protection class IP 65

Weight: 11.0lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -40° C
LED module wattage 43.3 W
System wattage 50.0 W

Controllability 0-10V dimmable

Color rendering index Ra > 80 Luminaire lumens 4853 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:



Wall washer · Symmetric					
	LED	А	В	С	
B33388	43.3 W	121/2	5	85/8	

Type:

BEGA Product:

Project: Modified:

Available options

CUS Custom finish

FSC Fusing

MGU Marine grade undercoat

RAL RAL finish

