BEGA

Application

This wall luminaire has a symmetric light distribution on one side and a wide spread light distribution on the other side. The symmetric light distribution can be used to illuminate façade and wall surfaces, with the installation surface also acting as the reflection surface. The wide spread light distribution can be used to illuminate ground surfaces along walls.

Materials

Clear safety glass

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy High temperature silicone gasket

Mechanically captive stainless steel fasteners

Silicone applied robotically to casting, plasma treated for increased adhesion

Galvanized zinc-plated mounting bracket

Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations Protection class IP 65

Weight: 11.0lbs.

Electrical

Operating voltage 120-277VAC -30° C Minimum start temperature LED module wattage 33.7 W System wattage 41.0W

0-10V dimmable Controllability

Color rendering index Ra > 80 Luminaire lumens 4773 lm 60000 hrs LED service life (L70)

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ) Silver (SLV) White (WHT) RAL: CUS:

Wall washer · Symmetric upward · Lateral throw downward

	LED	А	В	С
B33393	33.7 W	93/,	61/,	73/,

Type:

BEGA Product:

Project: Modified:

Available options

CUS Custom finish

MGU Marine grade undercoat

RAL RAL finish

