

Application

This wall mounted luminaire has light output on two sides. Thick-walled crystal glass characterizes the design of this distinctive luminaire. Arranged individually or in groups, this is a great design element for a host of lighting applications.

Materials

Pressed crystal glass with white ceramic coating on one side  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners  
BEGA Hybrid Optics®

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 64

Weight: 1.4 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	5.8W
System wattage	8.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	290lm
LED service life (L70)	60000hrs

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:


Type:  
BEGA Product:  
Project:  
Modified:

Available options

CUS	Custom finish
MGU	Marine grade undercoat
RAL	RAL finish

Included (available for pre-shipment)

B19538	Small opening wiring box
--------	--------------------------



Wall luminaire · Light emission on two sides					
		LED	A	B	C
B33505	ADA	5.8W	3 1/2	4 3/4	4

