

Application

Ceiling and wall luminaire with shallow profile designed for general purpose illumination featuring crystal glass. This luminaire can be utilized individually or in groups for glare-free illumination in interior and exterior spaces.

Materials

Pressed crystal glass with white ceramic coating on one side
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 High temperature silicone gasket

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 64

Weight: 7.9 lbs.

Electrical

Operating voltage 120-277V AC
 Minimum start temperature -20° C
 LED module wattage 19.6 W
 System wattage 23.0 W
 Controllability 0-10V dimming down to 0.1%
 Color rendering index Ra > 90
 Luminaire lumens 1937 lm
 LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3)
 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
 Silver (SLV) White (WHT)
 RAL: CUS:

Available options

CUS Custom finish
 FSC Fusing
 MGU Marine grade undercoat
 RAL RAL finish



Ceiling and wall luminaire · Crystal glass

		LED	A	B
B33683	ADA	19.6 W	12	2 ⁵ / ₈

