

Application

Luminaires with direct and indirect light, to illuminate both the mounting surface and the desired space. Luminaires in this series are also available with an identical cover made of impact-resistant synthetic material for special applications, add P suffix to luminaire catalog number.

Materials

Hand-blown three-ply opal glass
 Aluminum housing
 Fully potted waterstopper cable
 Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, for interior use only

Weight: 6.8 lbs.

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -30° C
 LED module wattage 16.4 W
 System wattage 19.3 W
 Controllability 0-10V dimmable
 Color rendering index Ra > 80
 Luminaire lumens 1333 lm
 LED service life (L70) 60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

- White (.1)
- Silver (.2)

Type:
 BEGA Product:
 Project:
 Modified:



Ceiling and wall luminaire · Opal glass · Direct/Indirect

		LED	A	B	C
B34278	ADA	16.4 W	14 ¹ / ₄	3 ³ / ₈	10 ¹ / ₂

