

Application

This unshielded wall luminaire is made of stainless steel and hand-blown, three-ply opal glass. Arranged individually or in groups, it is a great design element for a host of lighting applications.

Materials

- Hand-blown three-ply opal glass
- 316 grade stainless steel
- High temperature silicone gasket
- Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 44

Weight: 2.0lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	1.9W
System wattage	5.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	285lm
LED service life (L70)	60000hrs


LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.



Wall luminaire · Unshielded

		LED	A	B	C	D
B44009	ADA	1.9W	2 ³ / ₄	14 ⁷ / ₈	4	3

Type:

BEGA Product:

Project:

Modified:

Available options

- FSC
- Fusing

Included (available for pre-shipment)

- B19538
- Small opening wiring box

