

**Application**

The wall mounted luminaire has light output on two sides. Arranged individually or in groups, this is a great design element for a host of lighting applications.

**Materials**

Clear safety glass with matte finish  
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 High temperature silicone gasket  
 Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 28.0lbs.

**Electrical**

Operating voltage 120-277VAC  
 Minimum start temperature -30° C  
 LED module wattage 30.4 W  
 System wattage 36.0 W  
 Controllability 0-10V dimmable  
 Color rendering index Ra > 80  
 Luminaire lumens 2123lm  
 LED service life (L70) 60000hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

- Black (BLK)                      Bronze (BRZ)
- Silver (SLV)                     White (WHT)
- RAL:                                CUS:

Type:

BEGA Product:

Project:

Modified:

**Available options**

- CUS                      Custom finish
- MGU                     Marine grade undercoat
- RAL                      RAL finish

**Included (available for pre-shipment)**

- B19537                Narrow opening wiring box



**Wall luminaire · Light emission on two sides**

	LED	A	B	C
<b>B44438</b>	30.4 W	59 <sup>7</sup> / <sub>8</sub>	4 <sup>1</sup> / <sub>8</sub>	5

