Application

Compact wall luminaires with light emission in two directions. Thick-walled brilliant crystal glass characterizes the design of these luminaires. Whether as single luminaires or aligned in rows, they illuminate and accentuate many features in the room.

Materials

Pressed crystal glass with white ceramic coating on one side Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy Pure anodized aluminum reflector

NRTL listed to North American Standards, for interior use only

Weight: 2.2 lbs.

Electrical

Operating voltage 347V AC
Minimum start temperature -40° C
LED module wattage 7.6W
System wattage 9.5W

Controllability 0-10V dimmable

Color rendering index Ra > 80 Luminaire lumens 542 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

White (.1) Velvet black (.5) Palladium (.4)

Type:

BEGA Product:

Project: Modified:

Included (available for pre-shipment)

B19538 Small opening wiring box





Wall luminaire · Light emission on two sides

LED A B C
B50063 ADA 7.6W 3¹/₂ 4³/₄ 4