

**Application**

Wall luminaires for a host of applications – arranged individually or in groups. An inner mechanism allows the glass to be swiveled in and out for re-lamping so they can also be installed horizontally or vertically in niches between walls.

**Materials**

Hand-blown three-ply opal glass  
Aluminum housing

**NRTL** listed to North American Standards, for interior use only

**Weight:** 7.3 lbs.

**Electrical**

Operating voltage                    120-277VAC  
Minimum start temperature       -20° C  
LED module wattage                23.6W  
System wattage                        27.5W  
Controllability                        0-10V dimming down to 0.1%  
Color rendering index                Ra > 80  
Luminaire lumens                      2619lm  
LED service life (L70)                60000hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

Select the desired material finish by using appropriate code number as suffix.

**Available colors**

- Stainless steel (.2)
- Chrome (.3)

Type:

BEGA Product:

Project:

Modified:



**Linear wall luminaire · Opal glass**

	LED	A	B	C
<b>B50069</b>	23.6W	27 <sup>3</sup> / <sub>4</sub>	3 <sup>1</sup> / <sub>8</sub>	4 <sup>1</sup> / <sub>2</sub>

**Included (available for pre-shipment)**

B19537      Narrow opening wiring box

