## Application

Wall luminaires for a host of applications – arranged individually or in groups. An inner mechanism allows the glass to be swiveled in and out for re-lamping so they can also be installed horizontally or vertically in niches between walls.

### Materials

Hand-blown three-ply opal glass

Aluminum housing

NRTL listed to North American Standards, for interior use only

Weight: 9.7 lbs.

Electrical

Operating voltage 120-277VAC
Minimum start temperature -20° C
LED module wattage 35.4 W
System wattage 41.0 W

Controllability 0-10V dimming down to 0.1%

Color rendering index Ra > 80 Luminaire lumens 3930 lm LED service life (L70) 60000 hrs

# LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

#### Finich

Select the desired material finish by using appropriate code number as suffix.

### Available colors

Stainless steel (.2) Chrome (.3)

Type:

**BEGA Product:** 

Project: Modified:

## Included (available for pre-shipment)

B19537 Narrow opening wiring box





Linear wall luminaire · Opal glass					
	LED	Α	В	С	
B50070	35.4 W	391/2	31/8	41/2	