

Application

Ceiling and wall luminaires designed for general purpose illumination for interior locations featuring a shallow depth and hand-blown, three-ply opal glass with satin matte finish.

Materials

Hand-blown opal glass
 Aluminum housing
 Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, for interior use only

Weight: 12.8lbs.

Electrical

Operating voltage 120, 240 or 277VAC
 Minimum start temperature -30° C
 LED module wattage 60.1 W
 System wattage 69.5 W
 Controllability 0-10V dimmable
 Color rendering index Ra > 80
 Luminaire lumens 5228 lm
 LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3)
 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

White finish. Custom colors not available.

Type:

BEGA Product:


Project:

Modified:

Available accessories

- B13085 Trim ring · White
- B13086 Trim ring · Stainless steel
- B13087 Trim ring · Chrome

See individual accessory spec sheet for details.



Ceiling and wall luminaire · Opal glass

	LED	A	B
B50081	60.1 W	18 1/2	4 1/2

