

**Application**

Open wall luminaires with a high level of efficiency, characterized by an elongated design. As solid and reliable lighting tools with modern lamp technology and high-quality workmanship, they will provide very cost-effective service over long operating periods.

**Materials**

Hand-blown three-ply opal glass  
Aluminum housing

**NRTL** listed to North American Standards, for interior use only

**Weight:** 7.9 lbs.

**Electrical**

Operating voltage 120-277VAC  
Minimum start temperature -20° C  
LED module wattage 36.4 W  
System wattage 42.0 W  
Controllability 0-10V dimming down to 0.1%  
Color rendering index Ra > 80  
Luminaire lumens 4498 lm  
LED service life (L70) 60000 hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

White finish. Custom colors not available.



**Linear wall luminaire · Opal glass**

	LED	A	B	C
<b>B50085</b>	36.4 W	4 <sup>3</sup> / <sub>8</sub>	27 <sup>7</sup> / <sub>8</sub>	5 <sup>3</sup> / <sub>4</sub>

Type:  
BEGA Product:  
Project:  
Modified:

**Included (available for pre-shipment)**  
B19537 Narrow opening wiring box

